

PROFILATI A " U " SERIE SPECIALE

EU 54/80

EN 10025-2 - EN 10279

DESIGNAZ. mm.	SPESSORE ANIMA mm.	SPESSORE ALA mm.	PESO Kg/m.
25 x 12	4	4	1,30
30 x 15	5	5	2,20
35 x 17	5,5	5,5	2,52
40 x 20	6	6	3,23
50 x 25	6	6	4,15
60 x 30	6,5	6,5	5,45



PROFILATI A "U" SERIE ALLEGERITA

EN 10025-2 - EN 10279 - EU 54/80

DESIGNAZIONE mm.	PESO Kg/m.
30 x 15 x 4	1,74
40 x 20 x 5	2,94
50 x 25 x 5	3,86


PROFILATI A "UNP" SERIE NORMALE

EN 10279 - EU 54/80

DESIGNAZIONE mm.	SPESSORE ANIMA mm.	SPESSORE ALA mm.	PESO mm.
30 x 33	5	7	4,27
40 x 35	5	7	4,87
50 x 38	5	7	5,59
65 x 42	5,5	7,5	7,09
80 x 45	6	8	8,65
100 x 50	6	8,5	10,60
120 x 55	7	9	13,30
140 x 60	7	10	16,00
160 x 65	7,5	10,5	18,90
180 x 70	8	11	22,00
200 x 75	8,5	11,5	25,30
220 x 80	9	12,5	29,40
240 x 85	9,5	13	33,20
260 x 90	10	14	37,90
280 x 95	10	15	41,90
300 x 100	10	16	46,10
320 x 100	14	17,5	59,50
350 x 100	14	16	60,60
380 x 102	13,5	16	63,10
400 x 110	14	16	71,80

" UNP " NORMALI PROFILO

EN 10025-2 - EN 10279



EU 54/80

DESI GNAZ. mm.	PESO Kg/m.	SEZ. cmq.	DIMENSIONI					caratteristiche riferite all'asse neutro					
								X - X			Y - Y		
			h mm.	b mm.	a mm.	e mm.	r mm.	J_x cm ⁴	$\frac{J_x}{v_x}$ cm ³	I_x cm.	J_y cm ⁴	$\frac{J_y}{v_y}$ cm ³	I_y cm.
30	4,27	5,44	30	33	5	-	-	36,39	4,26	1,08	5,1	2,60	0,968
40	4,88	6,21	40	35	5	-	-	14,1	7,07	1,51	6,68	3,08	1,04
50	5,59	7,12	50	38	5	-	-	26,5	10,6	1,93	9,1	3,74	1,13
65	7,09	9,03	65	42	5,5	-	-	57,5	17,7	2,52	14,0	5,05	1,25
80	8,65	11,0	80	45	6	7,76	8	106	26,5	3,10	19,4	6,35	1,33
100	10,6	13,5	100	50	6	8,26	8,5	205	41,1	3,91	29,1	8,45	1,47
120	13,3	17,0	120	55	7	8,72	9	364	60,7	4,63	43,1	11,1	1,59
140	16,0	20,4	140	60	7	9,72	10	605	86,4	5,45	62,5	14,7	1,75
160	18,9	24,0	160	65	7,5	10,2	10,5	925	116	6,21	85,0	18,2	1,88
180	22,0	28,0	180	70	8	10,68	11	1354	150	6,96	113	22,4	2,01
200	25,3	32,2	200	75	8,5	11,16	11,5	1911	191	7,71	148	26,9	2,14
220	29,4	37,4	220	80	9	12,14	12,5	2691	245	8,48	196	33,5	2,29
240	33,2	42,3	240	85	9,5	12,62	13	3599	300	9,22	247	39,5	2,41
260	37,9	48,3	260	90	10	13,6	14	4824	371	10,0	317	47,8	2,56
280	41,9	53,4	280	95	10	14,6	15	6276	448	10,8	398	57,1	2,73
300	46,1	58,8	300	100	10	15,6	16	8028	535	11,7	493	67,5	2,90